

# UltraMaxO<sub>2</sub>

SENSING

ANALYSIS

DELIVERY

The UltraMaxO<sub>2</sub> helps oxygen concentrator service


technicians looking to **save on costs and time** when checking patient O<sub>2</sub> concentrators. With **integrated oxygen, flow, and outlet pressure monitoring** in a single device, this handheld device is easy to operate, store, and transport and does not require a traditional electrochemical sensor, which reduces the overall maintenance and minimizes the cost of ownership



## Part Numbers:

UltramaxO<sub>2</sub> .....R223P01-001  
 UltraMaxO<sub>2</sub> (International).....R223P01-002

## TECHNICAL SPECIFICATIONS



### Oxygen

Oxygen Measurement Range (from a concentrator) ..... 20.9 - 96%  
 Oxygen Measurement Accuracy ..... ±1.5% of full scale at constant temperature and optimal flow\*  
 Oxygen Measurement Resolution ..... 0.1% Oxygen

### Flow

Flow Measurement Range ..... 0 - 10 LPM  
 Flow Measurement Accuracy ..... ±0.2 LPM  
 Flow Measurement Resolution ..... 0.1 LPM

### Pressure

Pressure Measurement Range ..... 0.5 - 50 (PSI), 3.4 - 344 (kPa)  
 Pressure Measurement Accuracy ..... ±0.5% (PSI), ±0.5% (kPa)  
 Pressure Measurement Resolution ..... 0.1 (PSI), 0.1 up to 199, 1 from 200 to 344 (kPa)  
 Response Time ..... ≤17 seconds  
 Warm-up Time ..... < 1 second  
 Operating Temperature ..... 15°C - 40°C (59°F - 104°F)  
 Storage Temperature ..... -15°C - 60°C (5°F - 140°F)  
 Pressure ..... 800 - 1000 mBars  
 Humidity ..... 0 - 95% (non-condensing)  
 Power Requirements ..... 2 AA Alkaline batteries (2 x 1.5 Volts)  
 Battery Life ..... ≥ 1,100 hours (16,500 read cycles)  
 Low Battery Indication ..... \*Low Battery\* icon displayed on LCD  
 Dimensions ..... 3.16" x 5.10" x 1.04" (80.3mm x 129.5mm x 26.4mm)  
 Weight ..... 0.4 lbs (181 g)



2305 S 1070 W,  
 West Valley City, UT 84119

866.4.Maxtec

maxtec.com

# UltraMaxO<sub>2</sub>

## Quick Set-Up & Readouts

The UltraMaxO<sub>2</sub> displays quick, easy-to-see readings with an overall much shorter set up time. The user only needs to connect the tubing from the gas sample inlet on the UltraMaxO<sub>2</sub> directly to the oxygen concentrator. The LCD screen on the UltraMaxO<sub>2</sub> displays large, clear numbers of the readings.

## Reduced Cost of Ownership With The Ultrasonic Sensor

Because the UltraMaxO<sub>2</sub> does not require an oxygen sensor, there is no need to replace sensors over time. The built in ultrasonic sensor is designed to last the life of the analyzer, unlike a traditional galvanic oxygen sensor. This helps maintain a low cost of ownership because the costs associated with maintenance and regularly replacing the sensor are alleviated.

## Ability to Check Outlet Pressure

Having an integrated pressure monitor paired with %O<sub>2</sub> and flow measurement means that you only need one piece of equipment. Other products available potentially exclude this parameter, requiring use of additional equipment when servicing O<sub>2</sub> concentrators.



The design also makes checking outlet pressure extremely simple. Covering the outlet port with your finger will switch the reading from displaying %O<sub>2</sub> & flow rate to displaying the pressure of the O<sub>2</sub> concentrator.

There is also an added feature that allows the user to change the unit display for pressure from pounds per square inch to killipascal; this can be changed by using a switch inside the battery door.

## No In-Field Calibration Required

In some cases, medical device service technicians are required to record that they have calibrated the analyzer they are using to check equipment. The UltraMaxO<sub>2</sub> has a calibration verification button that verifies the unit is working correctly. When you hold down the button, it displays "cal ver" to confirm proper calibration, according to the products specifications. If there is an issue with the calibration (i.e. end of life, internal debris, etc.), it will display an error code to let the technician know there is an issue.

Some products used for oxygen concentrator servicing recommend that users calibrate their analyzers at 100% O<sub>2</sub>. This requires tanks or bottles of 100% oxygen, and can become difficult to manage.

Using an ultrasonic solution like the UltraMaxO<sub>2</sub> means the gas is already calibrated and the calibration verification button eliminates the need for in-field calibration



## Confidence in What's Being Delivered

- The UltraMaxO<sub>2</sub> is lightweight, durable, and easy to transport. The small design fits comfortably in the palm of your hand or in your back pocket. It also has a protective silicone case for added durability which helps to avoid damage during transport

ML-0230 Rev H



2305 S 1070 W,  
West Valley City, UT 84119

866.4.Maxtec | maxtec.com